



**270-365-7881** 11319 US HWY 62 W Princeton, KY 42445





# **SOUTHERN BARNWOOD** 29053-6

Southern barnwood has a reddish brown color. The boards vary from light to dark. It has narrow boards with a few knots.

**COTTAGE** 29102–6
Cottage has a light brown color with darker streaks and wide boards. It has very few knots.



KNOTTY PINE 0005-3
Knotty Pine has a warm brown color like weathered pine. It has planks with knots and lots of saw marks.



### **HICKORY** 2602-1

Hickory has a dark brown color with the hardwood flooring look. It has narrow boards with some small knots and saw marks.





# Smoke gray is light gray with wide planks. It has some small knots and many sawmarks.

SMOKE GRAY 2639-5

TIMBER 2639-4
Timberi has a dark brown color and the boards do not vary much. It does show some saw marks.



### SYCAMORE 29150-1

Sycamore is darker brown with reddish hints and the color does vary from board to board. It does show some nice knots.



# Ashwood has a light brown color. It has a nice uniform color with some knots.

**ASHWOOD** 2641-2

## Cabin has a medium brown color with wide planks. It has darker knots and dark streaks running through the boards. **CABIN** 2641-3

# **CLASSIC BARNWOOD** 2602-2

Classic Barnwood has a hardwood flooring look. It has narrow boards that vary in color and has a grayish brown color.



## GRAY TIMBER 29055-7

Gray Timber has a dark gray color with light gray boards throughout. It has some large Knots.





## DRIFTWOOD 2002-3

Driftwood has a warm tones with a mix of dark and light colors. It has wide planks and lots of saw marks.




### TRIM PROFILES



### **REDUCER**

Size MM - 2400 x 45 x 7 Size Inch - 94.5 x 1.77 x 0.28



### **STAIR NOSING**

Size MM - 2400  $\times$  50  $\times$  26 Size Inch - 94.5  $\times$  1.97  $\times$  1.03



### **T MOULDING**

Size MM -  $2400 \times 45 \times 7$ Size Inch -  $94.5 \times 1.77 \times 0.28$ 

### ULTIMATE SHIELD SCRATCH RESISTANT UV COATING

10X STRONGER AT RESISTING SCRATCHES, STAINS AND ABRASIVES THEN REGULAR UV

20 MIL WEAR LAYER

PROTECTS THE HD FILM

HD PRINT FILM

WITH WIDE VARIATION

### STONE POLYMER COMPOSITE (SPC) CORE

100% WATERPROOF CORE 14F DROP LOCK SYSTEM 2000 KGS/M3 DENSITY 70% LIMESTONE

### HIGH DENSITY IXPE PAD UNDERLAYMENT

SUPERIOR TO EVA UNDERLAYEMNT ADVANCED SOUND REDUCTION PROVIDE EXTRA COMFORT DROP-LOCK SYSTEM

### PRODUCT SPECIFICATIONS

PLANK SIZE: 7.13" X 48" WITH MICRO BEVEL (9" X 48" AVAILABLE AS SPECIAL ORDER)

**CORE:** SPC (STONE POLYMER COMPOSITE)

THICKNESS: 5MM (WITH 1.0MM HIGH DENSITY PRE-ATTACHED UNDERPAD)

PROTECTION: ULTIMATE SHIELD SCRATCH, STAIN AND WEAR RESISTANT DOUBLE UV COATING

**WEAR LAYER:** 22MIL (0.55MM) | 20MIL (0.5MM)

VISUALS: ULTRA HD, NATURE INSPIRED REALISTIC WOOD

**SURFACE:** WOOD GRAIN EMBOSSED, IMPRESSIVE TEXTURES

CARTON: 10 PIECES, 23.8 SQFT | 55 CARTONS PER PALLET

**INSTALLATION: 14F LOCKING SYSTEM** 

**RESIDENTIAL WARRANTY: 25 YEAR LIMITED** 

**LIGHT COMMERCIAL WARRANTY: 10 YEAR LIMITED** 

### **ENDURANCE** TECH CORE

Featuring proprietary technology to create the ultimate strength SPC waterproof core, which provides over 2000kg m3 density. This results in a product that is structurally solid, impact resistant, extremely durable and guaranteed to last. We achieve this by utilizing a premium quality and completely safe formula which consists of 70% Natural Stone, Virgin pvc, as well as the highest grade polymers and minerals fused together under heat & high pressure using special tech Extruders. Our Core provides next level performance above and beyond competing products.

### **ULTIMATE SHIELD** TECHNOLOGY

Sets a new industry benchmark in surface protection. This Special UV Coating Technology provides superb performance in Scratch, Stain and Wear Resistance (10x Stronger Resistance then regular UV) It is sourced from an American company and found on all Europian Collection Products

			DIMENSIONS
Thickness		//////	$5.00 \text{ mm} \cdot t_{\text{max}} - t_{\text{min}} \le 0.50 \text{ mm}$
Length			1219.2 mm · I <sub>max</sub> - I <sub>min</sub> ≤ 0.50 mm
Width		////	$181.1 \cdot 0.10 \text{ mm} \cdot \text{w}_{\text{max}} - \text{w}_{\text{min}} \le 0.20 \text{ mm}$
			TOLERANCE
Squareness		EN 16511	≤ 0.20 mm
Straightness		EN 16511	≤ 0.30 mm / m
Flatness Crosswise		EN 16511	Concave: ≤ 0.15% · convex: ≤ 0.20%
Flatness Lengthwise		EN 16511	Concave: ≤ 0.50% · convex: ≤ 1.00%
Openings between Elements		EN 16511	Average: ≤ 0.15 mm · max: ≤ 0.20 mm
Height Difference between Elements		EN 16511	Average: ≤ 0.10 mm · max: ≤ 0.15 mm
			TEST
Abrasion Resistance Method B		EN 16511	≥ 3000 cycles
Impact Resistance		EN 16511	≥ 1200 mm
Micro Scratch Resistance		EN 16511	≤ MSR-A1
Stain	Group 1 & 2	EN 16511	GRADE 5
Resistance	Group 3	EN 16511	GRADE 4
Castor Chair Test		ISO 4918	No change in appearance after 25.000 cycles
Effect of Furniture Leg		EN 16511	No visible damage
Thickness Swelling		EN 16511	No swelling
Residual Indentation		EN 16511	≤ 0.20mm
Locking Strength		EN 16511	fl0,2 $\geq$ 1 kN/m (length); fs0,2 $\geq$ 1.5 kN/m (width)
Dimensional Stability		EN 16511	≤ 0.25%
			ENVIRONMENT
Emission of Formaldehyde		CDPH	PASS
			PHYSICAL BEHAVIOR
Fire Behavior		EN 13501-1	Bfl-s1
Slide Resistance		EN 13893	DS
Thermal Resistance		EN 12667	0.01 (m2K)/W
Electrostatic Behavior		EN 1815	Antistatic Floor Covering
		S	OUND ABSORPTION QUALITIES
Calculated Impact Insulation Class		ASTM E492-09	IIC 62
Calculated Sound Transmission Class		ASTM E90-09	STC 60

### PREMIUM QUALITY FLOORS

### BEAUTIFULLY CRAFTED & BUILT TO LAST

### WHY IS TRU STONE SPC THE BEST FLOORING CHOICE?

- Meets and Exceeds all European & North American Quality Standards
- 100% Waterproof
- · Pet Friendly
- Stain Resistant
- Impact Resistant
- Lifetime Residential Warranty
- Quick & Easy to Install
- Patented click locking system
- Easy to Maintain
- Scratch Resistant
- Digital Ultra HD Stunningly Beautiful Wood Visuals
- · Natural wood feel surface texture
- Healthy Flooring choice with no formaldehyde & no phalates & no heavy metals & no benzene & no plasticizes
- Intertek Clean Air Certified Flooring; which meets stringent indoor air quality emissions criteria

- Made from 70% Natural Stone & 30% combination of virgin pvc, minerals and stabilizers
- · Very affordable product and install cost
- Worry & Stress free maintenance
- Installs right over most hard & flat floors
- · Suitable with underfloor heating
- Conforms to room temperature
- · Fire Resistant
- Wear resistant
- Safe, slip resistant surface
- Sound Absorbing, built in high density underpad
- Antibacterial
- Premium Quality Products which meet and exceed ISO & CE & ASTM standards
- · Attractive & Informative Packaging
- Ultimate Shield Surface Coating; which provides industry leading and superb scratch, stain and wear resistance





### **HEALTHY**FLOORING CHOICE

Our uncompromising core values are to produce and supply superb quality products that promotes a healthy environment in any setting. Our SPC Rigid Core Floors have been tested by Intertek Sustainability and achieved Clean Air Gold Certification. In addition, the raw materials we use in production are also tested regularly by third party sources to ensure they meet and exceed the highest quality and health standards.

### FEEL COMFORTABLE KNOWING THAT OUR PRODUCTS:

- Are Completely safe to be used in various indoor applications.
- Meet the most stringent air quality emissions criteria.
- Do not contain harmful materials such as benzene, formaldehyde, phthalate, or heavy metals.
- Are Antibacterial; impeding the growth of bacteria, fungi and mold.
- Are ethically produced with recycling systems that produce zero manufacturing waste.



Easy Click Installation



100% Waterproof



Built In Premium IXPE Under Pad



Suitable With Underfloor Heating



Indent Resistant, Strong & Stable



Lay Over Existing Floors



**HD Design & Textures** 



Slip Resistant & Ultra Quiet



**Environmentally Friendly** 



Naturally Warmer



Meets All ISO & ASTM Quality



Wear Resistant



Hard to Inflame



Ultimate Shield Surface Coating



Stain Resistant



**Healthy Flooring Choice** 

PREMILIM EUROPEAN SPC RIGID CORE FLOORS £ TRIM PROFILES



**270-365-7881** 11319 US HWY 62 W Princeton, KY 42445